



Environmental Permitting (England and Wales) Regulations 2016

Variation Notice

To: Timpson Limited, Claverton Road, Wythenshawe, Manchester, M23 9TT

Corby Borough Council ("the Council"), in the exercise of the powers conferred upon it by Regulation 20 of the Environmental Permitting Regulations 2016 (the Regulations) hereby gives you notice as follows:

The Council has decided to vary the conditions of Permit Reference Number 46 in respect of the operation of an installation at the W M Morrison Store, Oakley Road, Corby, Northamptonshire, N18 8LH

The variation of the conditions of the permit and the date on which they are to take effect are specified in [Schedule 1] to this notice. A consolidated permit as varied by this notice is set out in [Schedule 2].

Signed on behalf of Corby Borough Council

A handwritten signature in black ink, appearing to be "M. S.", written over a diagonal line.

Date 6th February 2019

Environmental Protection and Private Sector Housing Manager
Authorised Officer of the Council

Schedule 1

<p>The variations to the permit which the Council has decided to make:</p>	<p>Date(s) on which the variation of the permit is to take place:</p>
<p>Remove all conditions and replace with:</p> <ol style="list-style-type: none"> 1. Operations must be carried out in such a manner that no more than 20 grams of solvent per kilogram of product cleaned and dried shall be emitted as measured and reported annually. The 20 grams includes all organic solvents used within the installation e.g. dry cleaning solvent, water-proofing solutions and spot cleaning solutions. 2. A weekly inventory of solvent usage, product cleaned and solvent waste sent for recovery or disposal shall be maintained and held on site for inspection by the Regulator for at least 12 months. Further, the Operator should retain records of solvent purchased for at least 12 months. 3. A copy of the monthly inventory sheets shall be sent to the Regulator once yearly on 31st January. 4. The Regulator shall be advised in writing 14 days prior to any proposed significant alteration to the operation, or modification of the installation which may have an effect on emissions of VOC from the installation. 5. All operating staff shall know where the operating manual for each dry cleaning machine can be found and have ready access to it. 6. All operating staff shall be trained in the operation of each dry cleaning machine and the control and use of dry cleaning solvents. The training received shall be recorded. 7. The machine shall be installed and operated in accordance with supplier recommendations, so as to minimise the release of VOC to air, land and water. 8. In the case of abnormal emissions, malfunction or breakdown leading to abnormal emissions the operator shall: <ol style="list-style-type: none"> a. investigate immediately and undertake corrective action; adjust the activity to minimise those emissions; and b. adjust the activity to minimise those emissions; and c. promptly record the events and actions taken d. In this condition abnormal emission will include any detectable solvent smell other than in the area of the dry cleaning machine. 9. In cases of non-compliance causing immediate danger to human health, or threatens to cause an immediate significant adverse effect upon the environment, operation of the activity shall be suspended; and the Regulator informed within 24 hours. 10. Dry cleaning machines shall be operated as full as the type of materials to be cleaned will allow. (for instance, full loads for light non delicates materials such as suits. Delicates and heavy materials, such as, wedding dresses and blankets may need to be cleaned in part loads). 	<p>With Immediate effect.</p>

11. Where cleaning solvents containing VOC are not received in bulk they shall be stored:
- a. in the containers they were supplied in with the lid securely fastened at all times other than when in use; and
 - b. within spillage collectors, of suitable size, made of impervious and corrosion-proof materials; and
 - c. away from sources of heat and bright light; and
 - d. with access restricted to only appropriately trained staff, and
 - e. the lids of the containers shall only be removed when the container is next to the cleaning machine ready for filling. Cleaning solvents shall be obtained in containers of a size which allows the entire container to be emptied into the machine at each topping up. Once emptied the lid of the container shall be replaced securely.

(Note: from a health and safety point of view: a well ventilated area should be used).

12. Spot cleaning with organic solvents or organic solvent borne preparations shall only be carried out if no other method of treating a particular stain on the material to be cleaned is available.

13. The dry cleaning machine loading door shall be kept closed when not in use.

(Note - Where an extract fan is fitted to maintain a negative pressure within the machine during unloading, the exhaust from this fan should be directed to a carbon adsorption filter prior to discharge to atmosphere).

14. The dry cleaning machine loading door shall be closed before the start-up of the machine, and kept closed at all times through the drying and cleaning cycle.

- All machines installed after 19 May 2005 shall have interlocks to prevent start-up of the machine until the loading door is closed and to prevent opening of the loading door until the machine cycle has finished and the cage has stopped rotating.

- All machines installed after 19 May 2005 shall have interlocks to automatically shut down the machine under any of the following conditions: cooling water shortage, failure of the cooling ability of the still condenser, failure of the cooling ability of the refrigeration system or failure in the machine heating system resulting in the inability to dry the load.

15. The still, button trap and lint filter doors shall be closed before the start-up of the machine and kept closed at all times through the drying and cleaning cycle.

- All machines installed after 19 May 2005 shall have interlocks to automatically shut down the machine if the still, button trap and lint filter doors are not properly closed.

16. The still shall have a thermostatic control device or equivalent with which to set a maximum temperature, in accordance with manufacturers' recommendations for the solvent used. (In those cases where several machines are supplied by a steam supply, where the operator can demonstrate that the maximum temperature can be controlled via the steam pressure controller, then this should be accepted by the local authority).

17. All new, and substantially refurbished machines, shall have a spillage tray with a volume greater than 110% of the volume of the largest single tank within the machine.

(Explanatory note that is not part of the permit conditions - This does not remove the need to comply with Health & Safety recommendations relating to the fitting of spill trays to existing machines.)

18. All machines installed after 19 May 2005 shall have a secondary water separator to minimise potential solvent losses. Where this is not an integral part of the machine then the operator should select and install a method that will achieve an equivalent degree of separation. [Where this is followed by a an activated carbon unit then the operator will need to demonstrate adequate procedures are in place to detect when the unit requires disposal via an acceptable route].

19. Prior to disposal, containers contaminated with solvent shall be stored with the lids securely fastened to minimise emissions from residues during storage prior to disposal, and labelled so that all that handle them are aware of their contents.

(Note - Empty containers should, where possible, be returned to the supplier.)

20. Solvent contaminated waste, for example still residues, shall be stored:

- a. in suitable sealed containers with the lid securely fastened at all times other than when in use; and
- b. on a suitable impervious floor; and
- c. away from any drains which may become contaminated with residues as a result of spillage,
- d. away from sources of heat and bright light; and
- e. with access restricted to only appropriately trained staff.

(Note 1 - From a health and safety point of view: a well ventilated area should be used.)

(Note 2 - A concrete floor, (if necessary coated with flooring paint), is seen as sufficient to demonstrate compliance with 'suitable impervious floor'.)

21. Equipment to clean up spillages shall be quickly accessible in all solvent handling and storage areas.

22. The Operator shall maintain records incorporating details of all maintenance, testing, repair work carried out on each dry cleaning machine and the scales used to weigh the loads, along with details of training required under condition 6. The records shall be made available within 7 days on request by the Regulator.

23. Spares and consumables in particular, those subject to continual wear shall be held on site, or should be available at short notice from guaranteed suppliers, so that plant breakdowns can be rectified rapidly.

Schedule 2

Permit reference number 56 as varied by this notice is hereby attached.

Corby Borough Council
Environmental Services
Working towards a Cleaner Environment

ENVIRONMENTAL PERMIT

Environmental Permitting (England and Wales) Regulations 2016

Installation address

Timpson Limited
c/o W M Morrison Store
Oakley Road
Corby
Northamptonshire
NN18 8LH

The above named company is permitted to operate a dry cleaning installation containing the dry cleaning machine:

Make	Model	Serial Number	Load Capacity	Date of Installation	Cleaning Solvent
Firbimatic	S2018	192C80152	18kg	December 2005	Perchloroethylene

subject to compliance with the following conditions:

Signed.......... Date.....

**Environmental Protection and Private Sector Housing Manager
Authorised Officer of the Council**

Contact Details: Corby Borough Council, Environmental Services,
Deene House, New Post Office Square, Corby, Northants,
NN17 1GD

Tel: 01536 464075 Email: env.services@corby.gov.uk

Permit Holder:	Timpson Limited
Installation Address:	c/o W M Morrison Store Oakley Road Corby Northamptonshire NN18 8LH
Registered Address of Company:	Timpson Limited Claverton Road Wythenshawe Manchester M23 9TT
Provenance	Date
Permit 'deemed' application	1 st November 2006
Permit Issued	26 th June 2007
Permit Re-issued	13 th May 2009
Permit Revised	17 th November 2011
Permit transferred – new Registered Office	13 th June 2016
Draft simplified Permit issued	13 th July 2018
Permit simplified	7 th August 2018
Permit varied	6 th February 2019

Conditions

1. Operations must be carried out in such a manner that no more than 20 grams of solvent per kilogram of product cleaned and dried shall be emitted as measured and reported annually. The 20 grams includes all organic solvents used within the installation e.g. dry cleaning solvent, water-proofing solutions and spot cleaning solutions.
2. A weekly inventory of solvent usage, product cleaned and solvent waste sent for recovery or disposal shall be maintained and held on site for inspection by the Regulator for at least 12 months. Further, the Operator should retain records of solvent purchased for at least 12 months.
3. A copy of the monthly inventory sheets shall be sent to the Regulator once yearly on 31st January.
4. The Regulator shall be advised in writing 14 days prior to any proposed significant alteration to the operation, or modification of the installation which may have an effect on emissions of VOC from the installation.
5. All operating staff shall know where the operating manual for each dry cleaning machine can be found and have ready access to it.
6. All operating staff shall be trained in the operation of each dry cleaning machine and the control and use of dry cleaning solvents. The training received shall be recorded.

7. The machine shall be installed and operated in accordance with supplier recommendations, so as to minimise the release of VOC to air, land and water.
8. In the case of abnormal emissions, malfunction or breakdown leading to abnormal emissions the operator shall:
 - a. investigate immediately and undertake corrective action; adjust the activity to minimise those emissions; **and**
 - b. adjust the activity to minimise those emissions; **and**
 - c. promptly record the events and actions taken
 - d. In this condition abnormal emission will include any detectable solvent smell other than in the area of the dry cleaning machine.
9. In cases of non-compliance causing immediate danger to human health, or threatens to cause an immediate significant adverse effect upon the environment, operation of the activity shall be suspended; and the Regulator informed within 24 hours.
10. Dry cleaning machines shall be operated as full as the type of materials to be cleaned will allow. (for instance, full loads for light non delicates materials such as suits. Delicates and heavy materials, such as, wedding dresses and blankets may need to be cleaned in part loads).
11. Where cleaning solvents containing VOC are not received in bulk they shall be stored:
 - a. in the containers they were supplied in with the lid securely fastened at all times other than when in use; and
 - b. within spillage collectors, of suitable size, made of impervious and corrosion-proof materials; and
 - c. away from sources of heat and bright light; and
 - d. with access restricted to only appropriately trained staff, and
 - e. the lids of the containers shall only be removed when the container is next to the cleaning machine ready for filling. Cleaning solvents shall be obtained in containers of a size which allows the entire container to be emptied into the machine at each topping up. Once emptied the lid of the container shall be replaced securely.

(Note: from a health and safety point of view: a well ventilated area should be used).

12. Spot cleaning with organic solvents or organic solvent borne preparations shall only be carried out if no other method of treating a particular stain on the material to be cleaned is available.
13. The dry cleaning machine loading door shall be kept closed when not in use.

(Note - Where an extract fan is fitted to maintain a negative pressure within the machine during unloading, the exhaust from this fan should be directed to a carbon adsorption filter prior to discharge to atmosphere).

14. The dry cleaning machine loading door shall be closed before the start-up of the machine, and kept closed at all times through the drying and cleaning cycle.
 - All machines installed after 19 May 2005 shall have interlocks to prevent start-up of the machine until the loading door is closed and to prevent opening of the loading door until the machine cycle has finished and the cage has stopped rotating.
 - All machines installed after 19 May 2005 shall have interlocks to automatically shut down the machine under any of the following conditions: cooling water shortage, failure of the cooling ability of the still condenser, failure of the cooling ability of the refrigeration system or failure in the machine heating system resulting in the inability to dry the load.
15. The still, button trap and lint filter doors shall be closed before the start-up of the machine and kept closed at all times through the drying and cleaning cycle.
 - All machines installed after 19 May 2005 shall have interlocks to automatically shut down the machine if the still, button trap and lint filter doors are not properly closed.
16. The still shall have a thermostatic control device or equivalent with which to set a maximum temperature, in accordance with manufacturers' recommendations for the solvent used. (In those cases where several machines are supplied by a steam supply, where the operator can demonstrate that the maximum temperature can be controlled via the steam pressure controller, then this should be accepted by the local authority).
17. All new, and substantially refurbished machines, shall have a spillage tray with a volume greater than 110% of the volume of the largest single tank within the machine.

(Explanatory note that is not part of the permit conditions - This does not remove the need to comply with Health & Safety recommendations relating to the fitting of spill trays to existing machines.)

18. All machines installed after 19 May 2005 shall have a secondary water separator to minimise potential solvent losses. Where this is not an integral part of the machine then the operator should select and install a method that will achieve an equivalent degree of separation. [Where this is followed by an activated carbon unit then the operator will need to demonstrate adequate procedures are in place to detect when the unit requires disposal via an acceptable route].
19. Prior to disposal, containers contaminated with solvent shall be stored with the lids securely fastened to minimise emissions from residues during storage prior to disposal, and labelled so that all that handle them are aware of their contents.

(Note - Empty containers should, where possible, be returned to the supplier.)

20. Solvent contaminated waste, for example still residues, shall be stored:
 - a. in suitable sealed containers with the lid securely fastened at all times other than when in use; and
 - b. on a suitable impervious floor; and
 - c. away from any drains which may become contaminated with residues as a result of spillage,
 - d. away from sources of heat and bright light; and
 - e. with access restricted to only appropriately trained staff.

(Note 1 - From a health and safety point of view: a well ventilated area should be used.)

(Note 2 - A concrete floor, (if necessary coated with flooring paint), is seen as sufficient to demonstrate compliance with 'suitable impervious floor'.)

21. Equipment to clean up spillages shall be quickly accessible in all solvent handling and storage areas.
22. The Operator shall maintain records incorporating details of all maintenance, testing, repair work carried out on each dry cleaning machine and the scales used to weigh the loads, along with details of training required under condition 6. The records shall be made available within 7 days on request by the Regulator.
23. Spares and consumables in particular, those subject to continual wear shall be held on site, or should be available at short notice from guaranteed suppliers, so that plant breakdowns can be rectified rapidly.

Site Location Plan



Timpson Limited
c/o W M Morrison Store
Oakley Road
Corby
Northamptonshire
NN18 8LH

Store Plan (within WM Morrison Store)

